

Equipment ID: Img-15
SHIMADZU MOBILEART PLUS

Elec/Dim similar to AMX as follows:

Dimensions (All measures are nominal):

**Height: 76 inches Width: 25-3/16 inches Length: 45-3/8 inches;
Weight: 1080 pounds**

1-2-2 Environmental Limits

1. Operating temperature range: 59 to 100 Degrees Fahrenheit (15 to 38 Degrees Celsius) at 80% non-condensing humidity.
2. Storage temperature range -40 to +140 Degrees Fahrenheit (-40 to +60 Degrees Celsius)
3. Maximum operating altitude: 8,000 feet (2440 meters).

1-3 Battery

1-3-1 Specifications

1. Nine 12.9 volt batteries connected in series provide approximately 116 volts at full charge.
2. Battery charger requires the following:
 - > For Models 2169360-7, 2169360-8, 2169360-9, 2169360-10, 2236420-7 & 2275938-7, 2236420-8 & 2275938-8, 2236420-9 & 2275938-9, 2236420-10 & 2275938-10: 120 Volts AC, 60 Hz at 6 A.
 - > For Models 2169360, 2169360-2, 2169360-3, 2169360-4, 2236420 & 2275938, 2236420-2 & Typical Manufacturer's Picture

- GE Healthcare's AMX-4+ analog X-ray system provides high-performance in a compact, easy-to-maneuver package.
- The rotating arm and tube simplify positioning and facilitate bedside studies, while the maintenance-free battery produces up to 50 high-quality exposures with a single charge.
- Dual drive motors and oversize casters facilitate movement; even in taxing environments.

166 Highland Park Dr. Bloomfield, CT 06002 U.S.A.

Tel: (860) 218-2575 Fax: (860) 218-2565 Email: soma@somatechnology.com

Rev 1 04/08

2275938-2, 2236420-3 & 2275938-3, 2236420-4 & 2275938-4 and 2275938-12, -13, -14, -15, -16, -17: 220/240 Volts AC, 50 Hz at 3.15 A.

> For Models 2169360-5, 2169360-6, 2236420-5 & 2275938-5, 2236420-6 & 2275938-6: 100 Volts AC, 50/60 Hz at 6 A.

Voltage must be maintained to +/-10% of the nominal value during charging.

