

Equipment ID: MF-14
Examination Table
Ritter 204

Ritter by Midmark 204 Manual Examination Table with Soft Touched and Stitched Upholstery Specifications



One-Piece Seamless Drawers

One-piece, seamless drawers have easy-to-clean rounded edges and are designed to contain spilled fluids, keeping them from other areas of the table to improve infection control.

Spacious Side Drawers

Three spacious side drawers provide plenty of storage volume for gowns, drapes and other items, yet are made to help organize your assortment of smaller supplies and bulk supplies. In addition, there are two front drawers for easy access to items during pelvic exams.

Stylish & Easy to Clean

The ergonomic design of the upholstered top is as soft and comfortable as it looks, leaving your patients feeling more relaxed. The seamless upholstery eliminates areas where dirt and bacteria can accumulate so clean-up is easier, faster and more effective.

Removable Top System

The one-piece, upholstered top can be easily removed without tools, allowing for thorough cleaning or a quick upholstery color change.

Enlarged Footstep

We increased the size of the footstep over 40 percent above the industry standard. This allows patients to feel more secure and get on the table more confidently...putting minimal strain and stress on physicians or their staff.

Storage Access and Volume

Our passthrough side drawers provide access to supplies from either side of the table and give you the ability to change your room configuration when you want to.

Specifications	
Height with upholstery:	32.13" (81.6 cm)
Patient Weight Capacity:	500 lb. (226.8 kg)
Electrical receptacle:	(115 VAC 5 AMPS Max.) Duplex, hospital grade electrical receptacle on left side
Soft Touch upholstery top:	28.5" W x 56.25" L (72.4 x 142.9 cm)

Paper Roll Holder:	Holds 21" x 3.5" Paper Roll (53.3 cm x 8.9 cm)
Length with footrest extended:	Two large – 9" W x 15" L x 1.1" D (22.9 cm x 38 cm x 2.9 cm) Two small – 6.6" W x 15" L x 1.1" D (16.8 cm x 38 cm x 2.9 cm)
Electrical:	115 VAC, 50/60 Hz, 5.0 AMPS (with receptacle) 115 VAC, 50/60 Hz, 5.5 AMPS (with drawer heater) UL 60601-1 and Can/CSA 601.1-M90 Standard for Safety CE Mark