

Equipment ID: IT-15
HP LaserJet M3035 Multifunction Printer

**HP LaserJet M3035 Multifunction Printer (CC476A) -
Specifications and Warranty**

16.8 x 15.7 x 20.9 in

Input voltage: 110 to 127 VAC (+/- 10%), 60 Hz (+/- 2 Hz), 12
amp; 220 to 240 VAC (+/- 10%), 50 Hz (+/- 2 Hz), 6 amp
70.1 lb



Functions	
All-in-one functions	Print, copy, send-to email/network folder
Multitasking capability	Yes
Specifications	
Print speed, black (normal quality mode)	Up to 35 ppm
First page out (black)	As fast as 10 sec
Monthly duty cycle	Up to 75,000 pages
*Footnote for duty cycle	Duty cycle is defined as the maximum number of pages per month of imaged output. This value provides a comparison of product robustness in relation to other HP LaserJet or HP Color LaserJet devices, and enables appropriate deployment of printers and MFPs
Recommended monthly print volume	2000 to 6000 pages
*Footnote for recommended monthly print volume	HP recommends that the number of printed pages per month be within the stated range for optimum device performance, based on factors including supplies replacement intervals and device life over an extended warranty period.
Print technology	Laser
Print resolution, black	Up to 1200 x 1200 dpi
Print speed footnote	Speed specifications have been updated to reflect current industry testing methods.
Paper Handling	

Paper handling optional,input	Optional 500-sheet tray
Paper handling standard,input	500-sheet input tray, 100-sheet multi-purpose tray
Paper handling standard,output	250-sheet standard output bin
Envelope capacity	Up to 10 envelopes
Envelope feeder	No
Duplex printing (printing on both sides of paper)	Automatic (standard)
Document finishing	Sheetfed
Media sizes, standard	Letter, legal, executive
Media sizes, custom	Tray 1: 3 x 5 to 8.5 x 14 in; tray 2: 5.8 x 8.3 to 8.5 x 14 in
Media types	Paper (plain, inkjet, photo, banner), envelopes, labels, cards (index, greeting), overhead transparencies
Media weight	Multipurpose tray 1: 16 to 53 lb (straight through paper path for special media); 500-sheet input trays 2 and 3 (optional on M3035): 16 to 32 lb; ADF: 16 to 28 lb
Weight	60.6 lb
Additional Specifications	
Processor speed	400 MHz
Memory, standard	256 MB
Memory, maximum	256 MB
Print languages, standard	HP postscript level 2 emulation, PCL 5, PCL 6, PDF 1.5
Scanner specifications	
Scanner type	Flatbed, ADF
Scan resolution, optical	Up to 600 dpi
Bit depth	30-bit
Scan size, maximum (flatbed)	8.5 x 14 in
Scan size, maximum (ADF)	8.5 x 14 in
Scan speed (default)	Up to 32 ipm (600 x 300 mono)
Digital sending specifications	
Digital sending features	Send-to-e-mail, send-to-network folder, LDAP and SMTP authentication, LDAP addressing
Supported file formats	PDF, TIFF, PCL

Copier specifications	
Copy resolution, black	600 dpi
Copy reduce/enlarge settings	25 to 400%
Maximum number of copies	Up to 1000 copies
Fax specifications	
Faxing	No
Fax memory	Dependent on the amount of available disk space
Fax note	Based on standard ITU-T test image #1 at standard resolution. More complicated pages or higher resolution will take longer and use more memory.
Connectivity	
Connectivity, standard	1 Jetdirect inside 10/100 Base-T port; 1 foreign interface harness (FIH) port; 1 USB type A for adding accessories; 1 USB type B for printing; 1 open EIO slot
Connectivity, optional	HP Jetdirect Print Servers and HP Secure High Performance Hard Disk Drives. For more information on available HP networking solutions visit http://www.hp.com/go/jetdirect
Minimum system requirements	PC: Microsoft® Windows® 7 ready. For more information go to http://www.hp.com/go/windows7 . Some features may not be available. 133 MHz processor or higher, 64 MB RAM, 40 MB available hard disk space, USB or network port Macintosh: Mac OS 10.2 and higher; 128 MB RAM, 25 MB available hard disk space; network or USB port
Compatible operating systems	Microsoft® Windows® 7 ready. For more information go to http://www.hp.com/go/windows7 . Some features may not be available. Windows XP Home, Windows XP Professional, Windows XP Professional x64, Windows Server 2003, Windows 2000, Mac OS X v10.2.8, 10.3, 10.4, 10.5, 10.6, UNIX, Linux (see http://www.hplip.net)
Recommended Operating humidity range	30 to 70% RH
Operating temperature	59 to 90° F
Photo printing	
Display	Touch screen graphical display
Memory Card Compatibility	HP 64 MB 100-pin DDR DIMM Q7715A, HP 128 MB 100-pin DDR DIMM Q7718A, HP 256 MB 100-pin DDR DIMM Q7719A, HP 512 MB 100-pin DDR DIMM Q7720A
Dimensions and weight	
Dimensions (W x D x H)	16.8 x 15.7 x 20.9 in
Weight	60.6 lb

Package weight	70.1 lb
Power and operating requirements	
Power supply	Input voltage: 110 to 127 VAC (+/- 10%), 60 Hz (+/- 2 Hz), 12 amp; 220 to 240 VAC (+/- 10%), 50 Hz (+/- 2 Hz), 6 amp
Power consumption	600 watts (printing), 620 watts (copying), 28.4 watts (ready), 24 watts (sleep), 0.1 watts (off)
Power consumption (Active)	600 watts
Power Consumption (Standby)	280 watts
Power Consumption, Powersave	24 watts
Power Consumption (Manual-off)	0.1 watts
Power consumption footnote	Power requirements are based on the country/region where the printer is sold. Do not convert operating voltages. This will damage the printer and void the product warranty.
Acoustic Pressure Emissions	56 dB(A)
Acoustic power emissions	6.5 B(A)
Recommended Operating humidity range	30 to 70% RH
Operating temperature range	63 to 77° F
ENERGY STAR® Qualified	Yes
What's included	
What's in the box	HP LaserJet M3035 MFP; Power cord; Control panel overlay; HP LaserJet Black Print cartridge; CD with software and documentation; Getting started guide; Support flyer; Wall poster
Cable included?	No, please purchase USB cable separately
Warranty	One-year, on-site warranty; 24-hour, 7-days-a-week phone support